



Harmonised Product Standard

**EN 14351-1:2006+A2:2016**

## **Declaration of Performance**

Type of construction product:

Entrance doors and Patio doors

**Natre Nordic Edge**

**Inward opening, Wood/Alu, Flush internal frame and sash**

DOP nr.:

**D-Eu-MO-FI-WA-20260501**

The performance of the Entrance doors and Patio doors in the product line Natre Nordic Edge Inward opening, Wood/Alu, Flush internal frame and sash are in conformity with the performances declared on the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.

System of assessment and verification of constancy of performance of the construction product:  
(AVCP) System 3

Intended use:

For domestic and commercial buildings

Manufacturer:

**DOVISTA A/S**

Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):

NB 1071 - SINTEF AS, SINTEF Community, Norway

Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

Date:

30 april 2026

---

Horsens

Signed on behalf of DOVISTA A/S

---

Allan Lindhard Jørgensen  
CEO, DOVISTA A/S

**Declaration of Performance Natre Nordic Edge; Inward opening, Wood/Alu, Flush internal frame and sash**

**D-Eu-MO-FI-WA-20260501**

	<b>4.2</b> Resistance to windload	<b>4.5</b> Water tightness	<b>4.6</b> Dangerous substances	<b>4.8</b> Load bearing capacity of safety devices	<b>4.11</b> Acoustic performance	<b>4.12</b> * Thermal transmittance coefficient	<b>4.13</b> * Radiation properties	<b>4.14</b> Air permeability
<b>Opening function</b>								
<b>CDI</b>	<b>Casement door, inward opening, 1-leaf</b>							
Declared value	Class C4 (1600 Pa)	NPD	None	N/A	NPD	0,77 (W/m <sup>2</sup> K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	-	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	-	-	-	-	EN ISO 10077-2: 2017	-	EN 1026:2016
Notified body	NB 1071	-	-	-	-	NB 1071	-	NB 1071
Test report	102031756 / 2025-00524	-	-	-	-	102029797 / 2023-00856	102029797 / 2023-00856	102031756 / 2025-00524
Tested size (mm), WxH	1200 x 2500	-	-	-	-	1230 x 2180	-	1200 x 2500
<b>CDI-2</b>	<b>Casement door, inward opening, 2-leaf</b>							
Declared value	Class C3 (1200 Pa)	Class 9A (600 Pa)	None	N/A	NPD	0,77 (W/m <sup>2</sup> K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2017	-	EN 1026:2016
Notified body	NB 1071	NB 1071	-	-	-	NB 1071	-	NB 1071
Test report	102030359 / 2023-01436	102030359 / 2023-01436	-	-	-	102029797 / 2023-00856	102029797 / 2023-00856	102030359 / 2023-01436
Tested size (mm), WxH	1992 x 2430	1992 x 2430	-	-	-	2400 x 2180	-	1992 x 2430

\*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

\*\* Declared values see sheet "4.11, Acoustic performance"