



Harmonised Product Standard

EN 16034:2014
EN 14351-1:2006+A2:2016

Declaration of Performance

Type of construction product:
Facade windows and Casement doors

Natre Nordic Edge
Fixed Light, Wood/Alu
Fire element EI30

DOP no.:

W-GNP-WA-EI30-FL-20260501

The performance of the Facade windows and Casement doors in the product line Natre Nordic Edge; Fixed Light, Wood/Alu are in conformity with the declared in the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.
System of assessment and verification of constancy of performance of the construction product: (AVCP)
System 1 – for fire resistance and/or smoke control characteristics, EN 16034:2014, NB 1071/2253
(AVCP) System 3 – for general performance, EN 14351-1:2006+A2:2016, NB 1071

Intended use:

For domestic and commercial buildings

DOVISTA A/S

Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):

NB 1071 - SINTEF AS, SINTEF Community, Norway
NB 1071/2253 - SINTEF AS, SINTEF Community, Norway/GRYFIT Lab., Poland


Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

Date:

30 april 2026

Horsens

Signed on behalf of DOVISTA A/S



Allan Lindhard Jørgensen
CEO, DOVISTA A/S

Declaration of Performance Natre Nordic Edge; Fixed Light, Wood/Alu

W-GNP-WA-EI30-FL-20260501

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability	4.4 Fire Performance
Opening function				Sys. 3, EN 14351-1					Sys. 1, EN 16034

FL	Fixed light								
Declared value	Class C4 (1600 Pa)	E1500 (1500 Pa)	None	N/A	NPD	0,68 (W/m ² K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)	EI30
Classification standard	EN 12210:2016	EN 12208:2000(A)	-	-	-	EN 14609:2004	EN 410:2011	EN 12207:2016	EN 13501-2:2023
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	EN ISO 10077-2: 2003/2012	EN 410:2011	EN 1026:2016	EN 1364-1:2015
Notified body	NB 1071	NB 1071	-	-	-	NB 1071	NB 1071	NB 1071	NB 1071/2253
Test report	102031756/2025:00533	102031756/2025:00533	-	-	-	2023:00856/2023-Sep.	2023:00856/2023-Sep.	102031756/2025:00533	LBO-1696-23E-egz 1-W1
Tested size (mm), WxH	2670 x 2670	2670 x 2670	-	-	-	1230 x 1480	-	2670 x 2670	1417 x 2500
Classification report	-	-	-	-	-	-	-	-	LBO-1696-K-23E-egz 1-W1
Certificat	-	-	-	-	-	-	-	-	PS 3901

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A2:2016.

** Declared values see sheet "4.11, Acoustic performance"

*** The value is a calculated value, derived from the tested size in the ITC report and proportionally adjusted to a standard size.