



Harmonised Product Standard

EN 14351-1:2006+A2:2016

Declaration of Performance

Type of construction product:

Facade windows and Casement doors

Natre Nordic Edge

Inward opening, Wood/Alu, Flush internal frame and sash

DOP nr.:

W-Eu-MO-FI-WA-20260501

The performance of the Facade windows and Casement doors in the product line Natre Nordic Edge Inward opening, Wood/Alu, Flush internal frame and sash are in conformity with the performances declared on the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.

System of assessment and verification of constancy of performance of the construction product:
(AVCP) System 3

Intended use:

For domestic and commercial buildings

Manufacturer:

DOVISTA A/S

Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):

NB 1071 - SINTEF AS, SINTEF Community, Norway

NB 0402 - RISE RESEARCH INSTITUTES, Sweden


Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

Date:

30 april 2026

Horsens

Signed on behalf of DOVISTA A/S



Allan Lindhard Jørgensen
CEO, DOVISTA A/S

Declaration of Performance Natre Nordic Edge; Inward opening, Wood/Alu, Flush internal frame and sash

W-Eu-MO-FI-WA-20260501

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
Opening function								
BHI	Bottomhung window, inward opening							
Declared value	NPD	Class 9A (600 Pa)	None	N/A	**	0,80 (W/m ² K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	-	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	-	EN 1027:2016	-	-	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2017	-	EN 1026:2016
Notified body	-	NB 1071	-	-	NB 0402	NB 1071	-	NB 1071
Test report	-	102029604 / 2023-00907	-	-	**	102029797 / 2023-00856	102029797 / 2023-00856	102029604 / 2023-00907
Tested size (mm), WxH	-	1280 x 2610	-	-	1230 x 1480	1230 x 1480	-	1280 x 2610
COMBI-IN	Combination window, inward opening							
Declared value	Class B3 (1200 Pa)	NPD	None	N/A	**	N/A	N/A	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	-	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	-	-	-	SS-EN ISO 10140-1:2021/2:2021	-	-	EN 1026:2016
Notified body	NB 1071	-	-	-	NB 0402	-	-	NB 1071
Test report	2024:01034/2024-Sep.	-	-	-	**	-	-	2024:01034/2024-Sep.
Tested size (mm), WxH	2400 x 2610	-	-	-	1230 x 1480	-	-	2400 x 2610
SHI	Sidehung window, inward opening							
Declared value	NPD	Class 9A (600 Pa)	None	N/A	**	0,80 (W/m ² K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	-	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	-	EN 1027:2016	-	-	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2017	-	EN 1026:2016
Notified body	-	NB 1071	-	-	NB 0402	NB 1071	-	NB 1071
Test report	-	102029604 / 2023-00907	-	-	**	102029797 / 2023-00856	102029797 / 2023-00856	102029604 / 2023-00907
Tested size (mm), WxH	-	1280 x 2610	-	-	1230 x 1480	1230 x 1480	-	1280 x 2610

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet "4.11, Acoustic performance"

Declaration of Performance Natre Nordic Edge; Inward opening, Wood/Alu, Flush internal frame and sash

W-Eu-MO-FI-WA-20260501

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
Opening function								
TITU	Tilt and turn window, inward opening							
Declared value	NPD	Class 9A (600 Pa)	None	N/A	**	0,80 (W/m ² K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	-	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	-	EN 1027:2016	-	-	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2017	-	EN 1026:2016
Notified body	-	NB 1071	-	-	NB 0402	NB 1071	-	NB 1071
Test report	-	102029604 / 2023-00907	-	-	**	102029797 / 2023-00856	102029797 / 2023-00856	102029604 / 2023-00907
Tested size (mm), WxH	-	1280 x 2610	-	-	1230 x 1480	1230 x 1480	-	1280 x 2610

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet "4.11, Acoustic performance"

Declaration Of Performance Natre Nordic Edge; Inward opening, Wood/Alu, Flush in

** 4.11 Acoustic performance - Rw (C;Ctr)

Glass / Panels	Test report	Opening window	Internal sash 6mm	Internal sash 10mm
4-20-4-20-4 Energy Std/Clear/Energy Std WE Grey W/Argon	O100282-1200861 A	34 (-2;-6)		
6-20-4-18-4 Energy Std/Clear/Energy Std WE Grey W/Argon	O100282-1200861 B	37 (-2;-7)		
8-20-4-16-4 Energy/Clear/Energy WE w. Argon	O100282-1200861 B	39 (-2;-7)		
8-16-4-16-8 Energy/Clear/Energy WE w. Argon	O100282-1200861 B	36 (-2;-3)		
8-18-4-16-6 Energy/Clear/Energy WE w. Argon	O100282-1200861 B	39 (-3;-5)		
10-18-4-14-6 Energy/Clear/Energy WE w. Argon	O100282-1200861 B	39 (-1;-4)		
8-18-4-16-6,8 Energy/Clear/Energy Lam WE w. Argon	O100282-1200861 B	44 (-2;-7)		
8-16-4-16-8,8 Energy/Clear/Laminated Sound Energy WE w. Argon	O100282-1200861 B	44 (-1;-4)		
8,8-16-4-14-8,8 Energy Std Lam Safe Sound/Clear/Energy Std Lam Safe WE	O100282-1200861 B	45 (-1;-5)		
12,8-14-4-12-8,8 Energy Std Lam Safe Sound/Clear/Energy Std Lam Safe So	O100282-1200861 B	47 (-1;-5)		
16,8-22-12,8 Clear Lam Safe Sound/Energy Std Lam Safe Sound WE w. Arg	O100282-1200861 B	48 (-1;-3)		