



Harmonised Product Standard

EN 14351-1:2006+A2:2016

Declaration of Performance

Type of construction product:
Facade windows and Casement doors

**Natre Nordic Edge
Outward opening, Wood/Alu**

DOP nr.:
W-No-MO-WA-20260501

The performance of the Facade windows and Casement doors in the product line Natre Nordic Edge Outward opening, Wood/Alu are in conformity with the performances declared on the following pages.

This Declaration of Performance is issued under the sole responsibility of DOVISTA A/S.

System of assessment and verification of constancy of performance of the construction product:
(AVCP) System 3

Intended use:
For domestic and commercial buildings

Manufacturer:

DOVISTA A/S

Bygholm Søpark 21D, 8700 Horsens, Denmark

Notified Bodies (Test institute):

NB 1071 - SINTEF AS, SINTEF Community, Norway
NB 0402 - RISE RESEARCH INSTITUTES, Sweden
NB 1235 - Technological Institute, Denmark


Windows and Doors containing Electrical and Electronic Equipment are in conformity with RoHS (Directive 2011/65/EU of the European Parliament and of the Council of 8 June 2011 on the Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment) as amended by Directive 2015/863/EU.

Date:

30 april 2026

Horsens

Signed on behalf of DOVISTA A/S



Allan Lindhard Jørgensen
CEO, DOVISTA A/S

Declaration of Performance Natre Nordic Edge; Outward opening, Wood/Alu

W-No-MO-WA-20260501

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
Opening function								
COMBI-OUT	Combination window, outward opening							
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	N/A	N/A	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	-	-	EN 1026:2016
Notified body	NB 1071	NB 1071	-	-	-	-	-	NB 1071
Test report	102031756/2025:00525	102031756/2025:00525	-	-	-	-	-	102031756/2025:00525
Tested size (mm), WxH	1490 x 2290	1490 x 2290	-	-	-	-	-	1490 x 2290
COMBI-OUT-s	Combination window, outward opening, split alu							
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	NPD	N/A	N/A	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	-	-	-	EN 1026:2016
Notified body	NB 1071	NB 1071	-	-	-	-	-	NB 1071
Test report	102031756/2025:00525	102031756/2025:00525	-	-	-	-	-	102031756/2025:00525
Tested size (mm), WxH	1490 x 2290	1490 x 2290	-	-	-	-	-	1490 x 2290
FL	Fixed light							
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	**	0,68 (W/m ² K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2000(A)	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2017	-	EN 1026:2016
Notified body	NB 1071	NB 1071	-	-	NB 0402	NB 1071	-	NB 1071
Test report	102031756 / 2025-00533	102031756 / 2025-00533	-	-	**	102029797 / 2023-00856	102029797 / 2023-00856	102031756 / 2025-00533
Tested size (mm), WxH	2670 x 2670	2670 x 2670	-	-	1230 x 1480	1230 x 1480	-	2670 x 2670

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet "4.11, Acoustic performance"

Declaration of Performance Natre Nordic Edge; Outward opening, Wood/Alu

W-No-MO-WA-20260501

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
Opening function								
FL-spl	Fixed light with split alu							
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	**	0,68 (W/m ² K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2000(A)	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2017	-	EN 1026:2016
Notified body	NB 1071	NB 1071	-	-	NB 0402	NB 1071	-	NB 1071
Test report	102031756 / 2025-00533	102031756 / 2025-00533	-	-	**	102029797 / 2023-00856	102029797 / 2023-00856	102031756 / 2025-00533
Tested size (mm), WxH	2670 x 2670	2670 x 2670	-	-	1230 x 1480	1230 x 1480	-	2670 x 2670
SGO	Side-guided window							
Declared value	NPD	Class 9A (600 Pa)	None	Class 4	**	0,80 (W/m ² K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	-	EN 12208:2016	-	EN 13115:2021	-	-	-	EN 12207:2016
Test standard	-	EN 1027:2016	-	EN 14609:2004	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2017	-	EN 1026:2016
Notified body	-	NB 1071	-	NB 1071	NB 0402	NB 1235	-	NB 1071
Test report	-	102031756 / 2025-00285	-	102031756 / 2025-00285	**	312375 / 2025-Mar.	312375 / 2025-Mar.	102031756 / 2025-00285
Tested size (mm), WxH	-	988 x 2088	-	988 x 2088	1230 x 1480	1230 x 1480	-	988 x 2088
SHO	Sidehung window							
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	N/A	**	0,80 (W/m ² K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	-	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2017	-	EN 1026:2016
Notified body	NB 1071	NB 1071	-	-	NB 0402	NB 1235	-	NB 1071
Test report	102031756 / 2025-00280	102031756 / 2025-00280	-	-	**	312375 / 2025-Mar.	312375 / 2025-Mar.	102031756 / 2025-00280
Tested size (mm), WxH	988 x 2088	988 x 2088	-	-	1230 x 1480	1230 x 1480	-	988 x 2088

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet "4.11, Acoustic performance"

Declaration of Performance Natre Nordic Edge; Outward opening, Wood/Alu

W-No-MO-WA-20260501

	4.2 Resistance to windload	4.5 Water tightness	4.6 Dangerous substances	4.8 Load bearing capacity of safety devices	4.11 Acoustic performance	4.12 * Thermal transmittance coefficient	4.13 * Radiation properties	4.14 Air permeability
Opening function								
TGO	Top-guided window							
Declared value	Class C3 (1200 Pa)	Class 9A (600 Pa)	None	Class 4	**	0,80 (W/m ² K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	EN 13115:2021	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	EN 14609:2004	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2017	-	EN 1026:2016
Notified body	NB 1071	NB 1071	-	NB 1071	NB 0402	NB 1235	-	NB 1071
Test report	102031756 / 2025-01066	102031756 / 2025-01066	-	102031756 / 2025-01066	**	312375 / 2025-Mar.	312375 / 2025-Mar.	102031756 / 2025-01066
Tested size (mm), WxH	1800 x 1600	1800 x 1600	-	1800 x 1600	1230 x 1480	1230 x 1480	-	1800 x 1600
THO	Tophung window							
Declared value	NPD	Class 9A (600 Pa)	None	N/A	**	0,80 (W/m ² K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	-	EN 12208:2016	-	-	-	-	-	EN 12207:2016
Test standard	-	EN 1027:2016	-	-	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2017	-	EN 1026:2016
Notified body	-	NB 1071	-	-	NB 0402	NB 1235	-	NB 1071
Test report	-	102031756 / 2025-00283	-	-	**	312375 / 2025-Mar.	312375 / 2025-Mar.	102031756 / 2025-00283
Tested size (mm), WxH	-	1988 x 998	-	-	1230 x 1480	1230 x 1480	-	1988 x 998
THRO	Tophung reversible window							
Declared value	Class C4 (1600 Pa)	Class 9A (600 Pa)	None	Class 4	**	0,80 (W/m ² K)	Gg 0,53 / LTg 0,74	Class 4 (±600 Pa)
Classification standard	EN 12210:2016	EN 12208:2016	-	EN 13115:2021	-	-	-	EN 12207:2016
Test standard	EN 12211:2016	EN 1027:2016	-	EN 14609:2004	SS-EN ISO 10140-1:2021/2:2021	EN ISO 10077-2: 2017	-	EN 1026:2016
Notified body	NB 1071	NB 1071	-	NB 1071	NB 0402	NB 1235	-	NB 1071
Test report	102031756 / 2025-00014	102031756 / 2025-00287	-	102031756 / 2025-00287	**	312375 / 2025-Mar.	312375 / 2025-Mar.	102031756 / 2025-00287
Tested size (mm), WxH	1988 x 1188	1988 x 1188	-	1988 x 1188	1230 x 1480	1230 x 1480	-	1988 x 1188

*Thermal transmission coefficient (4.12) and radiation properties (4.13) of a specific product is provided in quotations and order confirmations in accordance with EN 14351-1:2006+A1:2016.

** Declared values see sheet "4.11, Acoustic performance"

Declaration Of Performance Natre Nordic Edge; Outward opening, Wood/Alu

** 4.11 Acoustic performance - Rw (C;Ctr)

Glass / Panels	Test report	Opening window	Internal sash 6mm	Internal sash 10mm
4-20-4-20-4 Energy Std/Clear/Energy Std WE Grey W/Argon	O100282-1303230 A	35 (-2;-6)	-	-
6-20-4-18-4 Energy Std/Clear/Energy Std WE Grey W/Argon	O100282-1303230 A	38 (-2;-7)	-	-
4-20-4-18-6,4 Energy Std/Clear/Energy Std Lam Safe WE Grey W/Argon	O100282-1303230 A	39 (-2;-7)	-	-
6,4-20-4-18-4 Energy Std Lam Safe/Clear/Energy Std WE Grey W/Argon	O100282-1303230 A	39 (-2;-7)	-	-
6-18-6-16-6 Energy Std/Clear/Energy Std WE Grey W/Argon	O100282-1303230 A	35 (-2;-6)	-	-
4-20-4-18-6,8 Energy Std/Clear/Energy Std Lam Safe WE Grey W/Argon	O100282-1303230 A	39 (-1;-6)	-	-
6,8-20-4-18-4 Energy Std Lam Safe/Clear/Energy Std WE Grey W/Argon	O100282-1303230 A	39 (-1;-6)	-	-
8-18-4-16-6 Energy Std/Clear/Energy Std WE Grey W/Argon	O100282-1303230 A	38 (-2;-4)	-	-
4-18-4-18-8,8 Energy Std/Clear/Energy Std Lam Safe Sound WE Grey W/Ar	O100282-1303230 A	41 (-2;-7)	-	-
8,8-16-4-15-6 Energy Std Lam Safe Sound/Clear/Energy Std WE Grey W/Ar	O100282-1303230 A	42 (-2;-6)	-	-
8-18-4-15-8,8 Energy Std/Clear/Energy Std Lam Safe Sound WE Grey W/Ar	O100282-1303230 A	41 (-2;-7)	-	-
8-18-4-14-8,8 Energy Std/Clear/Energy Std Lam Safe Sound WE Grey W/Ar	O100282-1303230 A	42 (-1;-3)	-	-
8,8-16-4-16-6,8 Energy Std Lam Safe Sound/Clear/Energy Std Lam Safe WE	O100282-1303230 A	43 (-2;-6)	-	-
8,8-16-4-14-8,8 Energy Std Lam Safe Sound/Clear/Energy Std Lam Safe WE	O100282-1303230 A	43 (-1;-3)	-	-
8,8-14-4-16-8,8 Energy Std Lam Safe Sound/Clear/Energy Std Lam Safe Sou	O100282-1303230 A	43 (-0;-2)	-	-